

L6000 Mono Laser optional paper handling



HL-L6300DW
STANDARD CAPACITY
OUTPUT = 250
INPUT = 570

DCP-L6600DW
STANDARD CAPACITY
OUTPUT = 250
INPUT = 570

MFC-L6800DW
STANDARD CAPACITY
OUTPUT = 250
INPUT = 570

HL-L6300DWT
STANDARD CAPACITY
OUTPUT = 250
INPUT = 1,090

MFC-L6800DWT
STANDARD CAPACITY
OUTPUT = 250
INPUT = 1,090



LT-5505 (INPUT OPTION)
• 250 sheet optional paper tray
• 3 on the HL and 2 on the DCP/MFC

TOTAL CAPACITY
= 1,320 (HL)
= 1,070 (DCP/MFC)



LT-6505 (INPUT OPTION)
• 520 sheet optional paper tray
• 2 x 520 sheet trays supported

TOTAL CAPACITY
= 1,610



TT-4000 (INPUT OPTION)
• 4 x 520 sheet tower tray with stabiliser base

TOTAL CAPACITY
= 2,650



MX-4000 (OUTPUT OPTION)
• 4 Bin Mailbox
• 100 Sheets x 4 Bins, convertible to 400 sheets x 2 Bins

TOTAL CAPACITY
= 1,050



LT-5505 (INPUT OPTION)
• 250 sheet optional paper tray
• 1 x tray supported only

TOTAL CAPACITY
= 1,340



LT-6505 (INPUT OPTION)
• 520 sheet optional paper tray
• 1 x tray supported only

TOTAL CAPACITY
= 1610